

CBL130

a unique blend of paraffin and soy waxes



A paraffin-soy blend designed for jar/container candles, offering single pour characteristics on small to medium candles and producing brilliant colors, outstanding scent throw, and premium candles.



CBL130 Recommendations

Additives

Always use UV additives to prevent photodegradation.

Color

We suggest heating the wax to 180° - 185° F to ensure that color will be completely dissolved.

Do not heat wax above 200° F, as natural waxes may turn yellow. Use color that is soluble in wax to prevent undissolved sediment in the wax. This sediment can block the wax flow in the wick and cause poor burning. Candlewic carries a full line of colors that are soluble in wax.

Fragrance

Add fragrance just before pouring to avoid fragrance loss. This will avoid prolonged heating of the liquid fragrance which could sacrifice the integrity of the concentration. We suggest starting out with 6% fragrance, but higher levels may be achieved depending on the fragrance.

Don't exceed more than 8% fragrance loads in your candle. Each fragrance has its own unique characteristics that may perform differently in waxes. Typically, heavier fragrances will have an adverse effect on your candle's burn. We suggest test burning your fragrance, wax and color combination to ensure you are getting an acceptable burn performance. You may need to adjust fragrance levels to achieve a desirable trade-off between fragrance and burn performance.

Pouring

It is always good practice to heat containers when possible to avoid surface chilling. Let candles cool at ambient temperature (do not force cool).

Wicking

The wick size is dependent upon the candle size, shape, type, and amounts of color and fragrance used. Any wick with that is treated with the NST2 treatment would be ideal. Treated wicks include the LX, CD, HTP, RRD, and ECO series.

Product Form

Bulk liquid and slabs.

Typical Properties

Melting Point
(ASTM D-87) 125-130°F

Penetration @ 25°C
(D-1321) 70-80 dmm



The Candlewic Company

3765 Old Easton Road | Doylestown, Pennsylvania 18901

Toll Free: 800-368-3352 | Local: 215-230-3601 | Fax: 215-230-3606 | www.candlewic.com